+86 0571 555 3535
Qian Tan Cheng Dong,
Jiande, Hangzhou,
Zhejiang Province
astra-chemical.com
info@astra-chemical.com

ASTRA F 2409

Functional additive

Description

ASTRA F 2409 is a multifunctional additive used as pigment wetting agent, adhesion promoter and drying accelerator in 2K and air dtying solvent-borne systems. It also could improve mechanical properties of the final coating due to additional interactions with active groups of the additive.

Physical and Chemical properties

Ingredient: Silane modified acrylate
Appearance: Transparent liquid
Active part: 30%

Specialty

1. ASTRA F 2409 could accelerate the drying process of the coating.
2. ASTRA F 2409 could improve mechanical properties of the coating.

Application System and Dosage

ASTRA F 2409 is suitable for 2K PU, acrylate, alkyd and epoxy coating systems.

The recommended dosage of the additive is around 0,1 - 2% upon total formulation. The optimal dosage should be determined after series of tests.

Package

25kg plastic pail.

The information herein is based on our present knowledge and experience. The information merely describes the properties of our products but no guarantee of properties in the legal sense shall be implied. We recommend testing our products as to their suitability for your envisaged purpose prior to use. No warranties of any kind, either express or implied, including warranties of merchantability or fitness for a particular purpose, are made regarding any products mentioned herein and data or information set forth, or that such products, data or information may be used without infringing intellectual property rights of third parties. We reserve the right to make any changes according to technological progress or further developments.