+86 0571 555 3535
Qian Tan Cheng Dong,
Jiande, Hangzhou,
Zhejiang Province
astra-chemical.com
info@astra-chemical.com

ASTRA WA 4203

Wetting agent

Description

ASTRA WA 4203 could reduce the surface tension of the system, improve flow and leveling. Also it could significantly increase smoothness and gloss of the paint film. It has excellent wettability and prevents coating defects like shrinkage and fish eyes. It prevents pigment floating and Benard cells formation.

Physical and Chemical properties

Ingredient: Modified polyorganosiloxane
Appearance: Colorless to light yellow transparent liquid
Active content: 100%

Speciality

1. ASTRA WA 4203 improves wetting and leveling of the system.
2. ASTRA WA 4203 prevents coating defects formation.
3. ASTRA WA 4203 has good compatibility.

Application System and Dosage

ASTRA WA 4203 is suitable for both water-borne and solvent-borne systems.

The recommended dosage of the additive is around 0.05 - 1.0% for solvent borne systems and around 0.05 - 0.5% for water borne systems. The optimal dosage should be determined through series of tests.

Package

25kg metal pail.

The information herein is based on our present knowledge and experience. The information merely describes the properties of our products but no guarantee of properties in the legal sense shall be implied. We recommend testing our products as to their suitability for your envisaged purpose prior to use. No warranties of any kind, either express or implied, including warranties of merchantability or fitness for a particular purpose, are made regarding any products mentioned herein and data or information set forth, or that such products, data or information may be used without infringing intellectual property rights of third parties. We reserve the right to make any changes according to technological progress or further developments.

ASTRA CHEMICAL COMPANY