

ASTRA LA 3401

Leveling agent

Description

ASTRA LA 3401 is a polyether modified polysiloxane with acrylic groups. It has excellent compatibility with most of common resins, it could provide excellent leveling and slip properties in UV curable systems.

Physical and Chemical properties

Ingredient: Polyether modified polysiloxane with acrylic groups

Appearance: Light yellow viscous transparent liquid

Active part: 100%

Speciality

Leveling	Wetting	Recoatibility	Compatibility	Sliding	Low Foam Stabilization	Anti-craters	Anti-blocking
●●●●●	●●●●	●●●●●	●●●●●	●●●●●	●●	●●●●	●●●●

●●●●● Good ● Bad

Application System and Dosage

ASTRA LA 3401 is suitable for UV curable coatings.

The recommended dosage of the additive is around 0.1 - 1% upon total formulation. It could be introduced at a random stage during the manufacture.

Package

25kg metal pail.

The information herein is based on our present knowledge and experience. The information merely describes the properties of our products but no guarantee of properties in the legal sense shall be implied. We recommend testing our products as to their suitability for your envisaged purpose prior to use. No warranties of any kind, either express or implied, including warranties of merchantability or fitness for a particular purpose, are made regarding any products mentioned herein and data or information set forth, or that such products, data or information may be used without infringing intellectual property rights of third parties. We reserve the right to make any changes according to technological progress or further developments.

