

ASTRA REO 10010

Rheology modifier

Description

ASTRA REO 10010 is a rheology modifier based on a water-borne polymer with hydrophobic groups. It could provide great anti-settling and anti-sagging properties. It has a pseudo plastic rheology profile. The additive is easy to introduce and is suitable for all kinds of water-borne systems as anti-sagging and anti-settling agent.

Physical and Chemical properties

Ingredient: Water-borne polymer with hydrophobic groups

Appearance: Light yellow transparent solution

Active part: 20%

Solvent: Water / 2-Butoxyethanol

Specialty

1. ASTRA REO 10010 is used in water-borne varnish systems. It could rapidly increase the viscosity and provide great anti-settling and anti-sagging properties to the system.
2. ASTRA REO 10010 could be used in a wide range of pH.

Application System and Dosage

ASTRA REO 10010 is suitable for all types of water-borne industrial coating systems.

The recommended dosage of the additive amount is 0.5-2.0% upon total formulation to prevent settling and 2.0-5.0% upon total formulation to prevent sagging.

ASTRA REO 10010 should be introduced at the terminal stage of the manufacture.

Package

25kg plastic pail.

The information herein is based on our present knowledge and experience. The information merely describes the properties of our products but no guarantee of properties in the legal sense shall be implied. We recommend testing our products as to their suitability for your envisaged purpose prior to use. No warranties of any kind, either express or implied, including warranties of merchantability or fitness for a particular purpose, are made regarding any products mentioned herein and data or information set forth, or that such products, data or information may be used without infringing intellectual property rights of third parties. We reserve the right to make any changes according to technological progress or further developments.

