

## ASTRA REO 4010

---

Rheology Modifier

### Description

ASTRA REO 4010 is a rheology modifier based on a dispersion of small sized polyamide wax particles with great anti-settling and anti-sagging properties. It creates highly thixotropic flow behavior. The additive is suitable for all types of solvent-borne systems as anti-sagging and anti-settling agent. Check the compatibility before using in a clear system.

### Physical and Chemical properties

**Ingredient:** Polyamide wax

**Appearance:** Milky white paste

**Active part:** 20%

**Solvent:** Xylene / alcohol

### Specialty

1. ASTRA REO 4010 is suitable for solvent-borne varnish systems. It can rapidly increase the viscosity and prevent sedimentation and increase anti-sagging properties.
2. ASTRA REO 4010 can be used in wood varnishes as anti-settling agent.

### Application System and Dosage

ASTRA REO 4010 is applied in all solvent-borne industrial coating systems.

The recommended dosage of the additive is 0.5% to 2.0% (as anti-settling agent) upon total formulation and 2.0% to 5.0% (as anti-sagging agent) upon total formulation. ASTRA REO 4010 should be introduced at the terminal stage of the manufacture.

### Package

**25kg** metal pail.

The information herein is based on our present knowledge and experience. The information merely describes the properties of our products but no guarantee of properties in the legal sense shall be implied. We recommend testing our products as to their suitability for your envisaged purpose prior to use. No warranties of any kind, either express or implied, including warranties of merchantability or fitness for a particular purpose, are made regarding any products mentioned herein and data or information set forth, or that such products, data or information may be used without infringing intellectual property rights of third parties. We reserve the right to make any changes according to technological progress or further developments.

