

ASTRA WA 1503

Wetting agent

Description

ASTRA WA 1503 is polyether modified organosilicone compound. It could greatly decrease the surface tension of the system and provide excellent substrate wetting ability. ASTRA WA 1503 provides low foam stabilization.

Physical and Chemical properties

Ingredient: Polyether modified polysiloxane

Appearance: Light yellow transparent liquid

Active part: 100%

Speciality

Leveling	Wetting	Recoatibility	Compatibility	Sliding	Low Foam Stabilization	Anti-craters	Anti-blocking
●●●●	●●●●	●●●●	●●●●	●	●●●●	●●●●	●

●●●● Good ● Bad

Application System and Dosage

ASTRA WA 1503 is suitable for water-borne systems (wood paints, industrial coating systems, UV curable systems and printing inks).

The recommended dosage of the additive is around 0.1-1% upon total formulation.

Package

25kg metal pail.

The information herein is based on our present knowledge and experience. The information merely describes the properties of our products but no guarantee of properties in the legal sense shall be implied. We recommend testing our products as to their suitability for your envisaged purpose prior to use. No warranties of any kind, either express or implied, including warranties of merchantability or fitness for a particular purpose, are made regarding any products mentioned herein and data or information set forth, or that such products, data or information may be used without infringing intellectual property rights of third parties. We reserve the right to make any changes according to technological progress or further developments.

